



TECHNICAL DATA SHEET

# OLI-NATURA Wood Care Wax

Liquid care wax based on natural oil/wax for the care and colour refreshment of oiled and waxed wood surfaces in interior areas. In natural - with a colour-enhancing appearance.

Colour	Assortment				
	Qty per pallet	3	60		
	Quantity per package	1 x 1 L	6 x 1 L	1 x 250 ml	24 x 250 ml
Colourless	A03675	☒	☒	☒	☒

- Area of application**
- Naturally oiled & oiled & waxed wood
  - Private & commercial
  - Solid wood furniture
  - Floors & stairs

- Properties**
- Initial care & refreshing of all naturally oiled & oiled & waxed wood surfaces
  - Universal – for wooden floors, stairs & furniture
  - Refreshes the colour and gives wood new protection
  - Dirt and water repellent, antistatic
  - Easy to apply with a cotton cloth, polishing pad, sprayer or mop
  - High yield: 1 litre is sufficient for approx. 50-100 m<sup>2</sup> per application
  - Suitable for toys, free from preservatives and fragrances

- Complies with/tested according to**
- Giscode Ö 60+
  - EU Decopaint compliant
  - DIN 71-3 (safety of children's toys)
  - DIN 53160 (saliva and sweat resistant)
  - Free from formaldehyde, aromatic compounds, biocides, preservatives, cobalt and oximes

**Notes**

Material, object and ambient temperature +15 to +30 °C.  
Shake or stir well before use!  
Mix containers from different batches before use.  
Remove excess material from the surface, avoid puddles.  
Carry out a preliminary test on exotic woods and veneers rich in active ingredients.  
Oxidative drying: Ensure that windows are open and air can circulate during and after processing.  
Risk of spontaneous combustion! Store oil-soaked rags under water or spread out in the open air to dry.

**Preparation**

Before any care measures, we recommend dry cleaning and damp cleaning with OLI-NATURA wood soap. Allow the surface to dry completely.

---

Shake the container well before use.

---

## Application

### Small areas (furniture)

- Soak a white pad or cotton cloth with wood care oil and polish into the wood.
- Within 10 minutes, remove the wet oil with a dry cotton cloth/oil absorbent cloth and polish. No excess oil should remain.
- Protect from water during the curing time and do not clean with a damp cloth.

### Large surfaces (floors):

- Apply the maintenance oil evenly and thinly using a sprayer or mop. Reapply oil to dry areas.
- Within 10 minutes, polish in the wet oil with a white or beige super hand pad under the pad holder for telescopic handles. Alternatively, you can use a single-disc machine. Polish until the surface appears even.
- Finally, polish the surface with a white Super Hand Pad or oil-absorbent cloth. No excess oil should remain on the surface.
- Protect from water during the curing time and do not allow to become damp.

**Consumption:** 1 coat, approx. 20-40 ml/m<sup>2</sup> per coat depending on the absorbency of the wood (approx. 25-50 m<sup>2</sup>/l). The application quantities vary depending on the sanding and type of wood.

**Drying:** Depending on humidity/temperature, the surface is dust dry after 1 hour, can be gently loaded after approx. 12 hours and is fully cured after 2-3 days. Protect from water and handle with care during this time.

### NOTE:

Consumption depends on the type of wood and the absorbency of the substrate. Excess material on non-absorbent areas delays drying, as do low temperatures and/or excessive humidity and/or excessive wood moisture.

The maintenance wax is recommended for refreshing oxidatively oiled surfaces. Do not use on UV-oiled finished parquet, as the maintenance oil requires an "open pore system". If in doubt, test on a concealed area first.

---

## Technical data

<b>Solid content:</b>	Low
<b>VOC</b>	550 g/l
<b>Colouring:</b>	High
<b>Colours:</b>	Natural (colourless/unpigmented)
<b>Hardener:</b>	-
<b>Applications:</b>	approx. 10-20 g/m <sup>2</sup> (1 litre approx. 50-100 m <sup>2</sup> per application)
<b>Application method:</b>	white polishing pad, oil-absorbent cloth or cotton cloth, squeegee
<b>Cleaning tools:</b>	Rinse tools immediately after use with the environmentally friendly OLI-NATURA brush cleaner or conventional OLI-NATURA oil thinner or white spirit. Dispose of cleaning residues properly.
<b>Storage life:</b>	Unopened, at least 36 months. Protect from frost.
<b>Disposal</b>	Empty containers and product residues must be disposed of in accordance with regional regulations.
<b>Declaration:</b>	Modified vegetable oils, linseed oil, wood oil, castor oil, carnauba wax, pharmaceutical-grade isoparaffin, lead- and cobalt-free drying agents, oxime-free anti-skinning agent.

---

---

**Care & cleaning** Regular cleaning with OLI-NATURA wood soap.  
Do not clean with a damp cloth or apply further care during the first 2-3 days while the oil is still hardening.

---

**Safety** No labelling required, not a hazardous substance. Further safety information can be found in the safety data sheet at [www.oli-lacke.de](http://www.oli-lacke.de).

---

Our written and verbal recommendations for use are only non-binding advice. They are based on our experience and current knowledge gained from practical application. They do not release the user from their responsibility to test our products themselves for their suitability for the intended purpose. All previous editions are hereby invalidated. Status: 18.11.24\_GS

---