



SCAN QR CODE
for datasheets, safety info –
available in multiple languages



TECHNICAL DATA SHEET

OLI-NATURA Yacht & Teak Oil

BIOCIDE-FREE WOOD OIL FOR OUTDOOR USE – PROTECTS TERRACES, GARDEN FURNITURE AND YACHT DECKS

Weather-resistant oil for hard and exotic woods for initial treatment and regular maintenance of terraces, garden furniture, pool surrounds and yacht decks – also suitable for pressure-impregnated softwoods. The wood oil penetrates deeply, dries quickly and protects the wood from the inside without cracking or flaking. Already oiled surfaces can be maintained and refreshed at any time by simply re-oiling. The lightly pigmented "Teak" variant offers increased UV protection and can be used universally on various types of wood. It is also available as a 6-piece **OLI-NATURA Care Set No. 5**. Free from biocides, therefore also suitable for indoor wood.

Colour	Item	Container / PU	Pallet
NATURAL (pigment-free)	A01397_RG	1 x 2.5 L	160
NATURAL (pigment-free)	A01397_RG_VE2	2 x 2.5 L	80
NATURAL (pigment-free)	A01397_RF	1 x 1 L	360
NATURAL (pigment-free)	A01397_RF_VE6	6 x 1 L	60
NATURAL (pigment-free)	A01397_RG	1 x 2.5 L	160
NATURAL (pigment-free)	A01397_TA	1 x 250 ml	
NATURAL (pigment-free)	A03675_TA_VE24	24 x 250 ml	
TEAK	A01398_RG	1 x 2.5 L	160
TEAK	A01398_RG_VE2	2 x 2.5 L	80
TEAK	A01398_RF	1 x 1 L	360
TEAK	A01398_RF_VE6	6 x 1 L	60
TEAK	A01398_RG	1 x 2.5 L	160
TEAK	A01398_TA	1 x 250 ml	
TEAK	A03678_TA_VE24	24 x 250 ml	
Care Set No. 5	A05339_SET	1 x set	

Colour	Item	Container / PU	Pallet
Care Set No. 5	A05339_SET_VE4	4 x 1 set	Contents: 250 ml teak oil in teak colour, 1 brush, 1 pad, 1 oil absorption cloth, 1 sanding sponge, care flyer

* Large containers and bulk containers available on request.

Area of application	<ul style="list-style-type: none"> ▪ Wood outdoors & indoors ▪ Private, commercial and industrial ▪ Hardwood and exotic wood as well as pressure-impregnated softwood ▪ Garden furniture & yacht decks ▪ Terraces and pool surrounds
Properties	<ul style="list-style-type: none"> ▪ Hardwood oil for easy application outdoors ▪ Weather-resistant and water-repellent ▪ Penetrates deep into the wood, effectively protecting it from UV rays, weathering, embrittlement and greying ▪ Suitable for untreated, open-pored oiled or newly sanded hardwood, exotic wood (including bangkirai, teak, eucalyptus and rubinie) and pressure-impregnated softwood
Complies with/tested according to	<ul style="list-style-type: none"> ▪ Gisode Ö 60+ ▪ EU Decopaint compliant ▪ DIN 71-3 (safety of children's toys) ▪ DIN 53160 (saliva and sweat resistant) ▪ Free from formaldehyde, aromatics, biocides, preservatives, cobalt and oximes
Notes	<ul style="list-style-type: none"> ▪ Only apply in dry weather and at temperatures between +15 and +25 °C. ▪ Do not use outdoors in direct sunlight, in high temperatures, high humidity or when there is a risk of rain. ▪ Cover adjacent areas such as paving or stone slabs with cardboard or plastic sheeting before starting work to prevent oil stains. ▪ Remove excess material from the surface and avoid puddles forming. ▪ Particularly in the case of renovations and on unknown substrates, it is advisable to test the product on an inconspicuous area. ▪ Risk of spontaneous combustion! Always store oil-soaked rags under water or spread them out to dry outdoors.
Wood preparation	<ul style="list-style-type: none"> ▪ The surface must be clean, dry and free of grease. For heavy soiling, we recommend cleaning with OLI-NATURA outdoor cleaner. ▪ Once completely dry, rough areas or raised fibres can be smoothed with fine sandpaper (220 grit) if necessary. ▪ Maximum wood moisture content: must not exceed 17%.
Application	<ul style="list-style-type: none"> ▪ Stir or shake the container well before use. ▪ Apply the oil thinly and evenly in the direction of the grain with a brush, roller or pad until the surface is completely covered. Reapply oil to dry areas. ▪ After approx. 15 minutes, remove excess oil: wipe off with a cotton or oil-absorbent cloth and polish. Alternatively, polish by hand or with a random orbital sander using a white polishing pad. The surface should then feel dry to the touch and not sticky. ▪ For highly absorbent or dried-out woods, a second coat can be applied as described above after drying overnight. Apply the second coat thinly and quickly as described.

TIP: Renovation coats (refreshers): one coat of oil is usually sufficient.

Consumption: 1-2 coats | Depending on the absorbency of the substrate, 40-80 g/m² per coat (12-25 m²/l). The application quantities vary depending on the sanding and type of wood.

Drying: Depending on humidity and temperature, the surface is dust-dry after 1-2 hours, can be gently used after 12 hours and is fully hardened after 5-8 days. During this time, protect from water, do not clean with a damp cloth and treat gently. At low temperatures and high humidity, the drying time is extended accordingly.

Care and cleaning

- **Maintenance intervals:** 1–2 times per year, depending on use, location and weather conditions.
- **Cleaning:** Clean thoroughly before re-oiling – optionally with **OLI-NATURA outdoor cleaner** (undiluted or diluted with water).
- **Protection in the initial period:** During the first **5–8 days**, while the oil is still hardening, it is essential to protect the surface from moisture and rain. Do not clean with a damp cloth during this period.

Technical data

Solid content:	Medium
VOC:	363 g/L – significantly below the EU limit values (Cat. A/f): 700 g/l (2010)
Brightening:	High
Colours:	Natural (pigment-free) emphasises the original colour tone, teak appears slightly pigmented and enhances UV protection.
Wood accent	Intensely emphasises the natural colour and grain of the wood.
Consumption:	1-2 coats with approx. 40-80 g/m ² (1 litre approx. 12-25 m ² per coat) Consumption varies greatly and depends largely on the type of wood and the weathering condition of the wood.
Application method:	Brush, roller, flat brush, cloth
Drying:	Dust dry: approx. 1-2 hours; recoatable: after drying overnight; fully cured: 5-8 days.
Cleaning of tools:	Rinse tools immediately after use with environmentally friendly OLI-NATURA brush cleaner or conventional OLI-NATURA oil thinner or white spirit. Dispose of cleaning residues properly.
Shelf life:	At least 36 months in original sealed container. Store in a cool, dry place protected from frost. Opened containers: Seal immediately and use promptly, as contact with air reduces shelf life.
Disposal:	Empty containers and product residues must be disposed of in accordance with regional regulations.
Declaration:	Modified vegetable oils, linseed oil, wood oil, castor oil, pharmaceutical-grade isoparaffin, lead- and cobalt-free drying agents, oxime-free anti-skinning agent, lightfast earth and mineral pigments
Safety:	No labelling required, not a hazardous material. Cloths, pads or sponges soaked in oil can self-ignite due to heat accumulation! Therefore, after use, store under water or moisten and spread out to dry outdoors before disposal. P102: Keep out of reach of children. Further safety information can be found in the safety data sheet at www.oli-lacke.de .

Our written and verbal recommendations regarding application technology are for guidance only. They are based on our experience and current knowledge from practical application. They do not release the processor from their responsibility to test our products themselves for their suitability for the intended use. All previous editions are hereby invalid. Status: 06092025_GS_SST
