TECHNICAL DATA SHEET

OLI NATURA® PreOilCleaner

WOOD PRE-TREATMENT BEFORE OILING AND BASIC CLEANER

PreOilCleaner prepares raw and freshly sanded interior timber for oiling, improves the oil absorption and colour effect of coloured oils, and reduces the risk of water and tannin stains. Also suitable for deep cleaning of oiled and soaped timber surfaces prior to further treatment.

Colour shade	**Range**				
	Qty per Palette	288	72		
	Quantity per pack	1 x	4 x	1 x	6 x
		1 L	1 L	250 ml	250 ml
Colourless	A05403	☒	☒	☒	☒

Scope of application	▪ Pre-treatment of untreated or freshly sanded wooden surfaces indoors prior to an oil finish. ▪ Deep cleaning of oiled and soaped timber surfaces indoors to remove stubborn dirt and residues from cleaning or care products that cannot be removed by normal cleaning.
Properties	▪ Prepares raw and freshly sanded wood for oiling ▪ Improves oil absorption and intensifies the colour when using coloured oils ▪ Reduces the risk of water marks and tannin stains during pre-treatment ▪ Dilute with lukewarm water: wood pre-treatment 1:4, deep cleaning 1:20
Complies with/Tested in accordance with	■ Complies with EU Decopaint standards ▪ Free from formaldehyde, aromatic compounds, biocides, preservatives, cobalt and oximes ▪ Giscode: GG20
Notes	Application temperature (material, surface and ambient): Wood pre-treatment +15 to +30 °C; basic cleaning +15 to +25 °C. Shake or stir well before use. Not suitable for regular routine cleaning. Reapply surface protection after basic cleaning. Test for compatibility and suitability on an inconspicuous test area and assess after complete drying, particularly with woods prone to swelling such as beech, maple or wood plaster. The surface must not be treated with PreOilCleaner prior to applying the OLI NATURA® Antique reactive stain. In the case of old layers of floor wax, thick maintenance coatings or very heavy soiling, renovation sanding may be necessary.
Wood preparation	Before the first oiling: sand the timber surface professionally and remove all dust thoroughly. Timber moisture content: 8–12 per cent. Before deep cleaning: Remove loose dirt and dust by vacuuming or sweeping.

Application

1. Pre-treatment of wood before initial oiling

1) Shake the bottle well. Mix 1 part PreOilCleaner with 4 parts lukewarm water (1:4), e.g. 100 ml of cleaner with 400 ml of water.
2) Apply evenly until the surface is slightly damp using a well-wrung cloth, sponge or cotton ball. A slightly damp mop is suitable for floors. Avoid leaving puddles. Repeat if the surface is heavily soiled.
3) Allow to dry completely: approximately 2–8 hours, or longer depending on conditions and the size of the area. The surface must look and feel evenly dry.
4) If necessary, lightly smooth any raised wood fibres in the direction of the grain using a fine-grit abrasive. Dust thoroughly and treat with an OLI NATURA® oil of your choice.

2. Basic cleaning prior to after-treatment

1) Shake the bottle well. Mix 1 part PreOilCleaner with 20 parts lukewarm water (1:20), e.g. 100 ml of cleaner with 2 litres of water. Have a second bucket of clean water ready.
2) Clean with a well-wrung cloth or mop until the surface is slightly damp and remove any loosened dirt. Rinse regularly in the second bucket and wring out well, then soak up more cleaning solution. Avoid puddles and standing water. Repeat if the surface is heavily soiled.
For heavier soiling, cleaning can be aided by using a single-disc machine with a cleaning pad suitable for the surface or a suitable cleaning brush. Work in sections and immediately remove the loosened dirt solution. Wipe with a slightly damp cloth using clean water and allow to dry completely.
3) Remove any remaining dirt and cleaning agent residues with fresh, clear water and a clean, well-wrung cloth or mop, dampened to a light mist.
4) Allow to dry completely: approximately 2–8 hours, or longer depending on conditions and the size of the area. The surface must look and feel uniformly dry.
5) Reapply surface protection: Re-oil oiled surfaces with a suitable OLI NATURA® oil. Treat soaped surfaces with a suitable wood floor soap. Follow the application instructions for the respective product.

Technical data

Colour:	Colourless
pH value (20 °C):	7.5
Density (20 °C):	0.98 g/cm³ (ISO 2811)
VOC:	163 g/l
Mixing ratio:	Wood pre-treatment 1:4; basic cleaning 1:20, in each case with water
Application method:	Sponge, mop, cotton pad, cloth
Drying time:	Approximately 2–8 hours, or longer if necessary. Allow to dry completely before further treatment.
Cleaning of ' ' tools:	With water
Storage / Shelf life of ' ':	At least 24 months unopened. Store in a cool, well-ventilated place, tightly sealed in the original container. Protect from frost, heat and direct sunlight.
Disposal:	Dispose of in accordance with local regulations. Do not allow to enter the mains drainage system or watercourses.

Safety

Not classified as hazardous in accordance with Regulation (EC) No 1272/2008. Not a dangerous good. Keep out of reach of children. Keep away from heat, sparks, open flames and other sources of ignition. No smoking. Keep container tightly closed.
Refer to the Safety Data Sheet at www.oli-lacke.de.

Our technical application recommendations, whether verbal or in writing, are provided for guidance only and are not binding. They are based on our experience and the current state of practical knowledge. They do not relieve the user of the responsibility to test our products themselves, at their own risk, to ensure they are suitable for the intended purpose.
All previous editions are hereby superseded. Date: 15 November 2026_V2_sst